



## Genes and Mechanisms for Improving Cellulosic Ethanol Production in *E. Coli*



### **Background**

Cellulosic biomass accounts for roughly 75% of all plant material, and can be used to produce biofuels. Sources of cellulosic biomass include agricultural plant waste, organic waste from industrial processes, and crops grown specifically for fuel production. Biological conversion makes use of enzymes and microorganisms to convert pretreated cellulosic biomass into biofuels. In particular, *Escherichia coli* is a well-studied microorganism commonly used in large-scale fermentations. In addition to biofuels, *E. coli* is capable of mass-producing platform chemicals as a replacement for traditional petrochemicals. Pretreatment of cellulosic biomass produces inhibitory compounds such as acetate and furfural. These compounds reduce fermentation efficiency, resulting in higher production costs. Engineering hardier biocatalysts to produce fuels and chemicals faster and cheaper is vital for biofuel and biorefining applications.

### **Technology**

A research group led by Dr. Ryan Gill of the University of Colorado has utilized genome-wide tools and analysis techniques to engineer bacterial strains with increased tolerance to acetate, furfural and ethanol, as well as strains with increased general tolerance to cellulosic hydrolysate. Acetate and furfural tolerance are important for efficient conversion of pretreated cellulosic biomass, and ethanol tolerance is important for the production of ethanol as a biofuel.



Some important ways tolerance has been engineered include: relieving metabolic burden of inhibited biosynthetic pathways, reducing the intracellular concentration of the inhibitory compound, and thwarting entrance of toxic compounds into the cell. This technology offers bacterial strains capable of tolerating industrially-relevant concentrations of acetate, furfural, and ethanol, along with other inhibitors found in cellulosic hydrolysate.

### **Advantages**

- ⇒ Hardier organisms with increased growth and production potential
- ⇒ Cost-efficient process for turning cellulosic biomass into useable biofuels
- ⇒ Can be applied to any bacteria capable of producing biofuels

### **Patent Applications:**



“Compositions and Methods for Enhancing Industrial Fermentation by Microorganisms,” May 1, 2009 (available under CDA).

“Compositions, Methods and Uses for Enhancing Aldehyde Tolerance by Microorganisms,” July 6, 2009 (available under CDA).

“Methods, Compositions and Uses for Modulating Gene Expression for Enhancing Hydrolysate Tolerance by Microorganisms,” June 4, 2010 (available under CDA).

UNIVERSITY OF  
COLORADO

TECHNOLOGY  
TRANSFER  
OFFICE

CU-Boulder/Colo. Springs  
4740 Walnut Street  
Suite 100  
Campus Box 589  
Boulder, CO 80309

(303) 492-5647

UC Denver  
12635 E. Montview Blvd  
Suite 350  
Campus Stop F411  
Aurora, CO 80045

303-724-0221

[http://www.cu.edu/  
techtransfer](http://www.cu.edu/techtransfer)

### **Status:**

Patents pending; available for  
exclusive or non-exclusive licensing.

### **Contact:**

Bryn Rees: 303-735-4474, [brynmor.rees@cu.edu](mailto:brynmor.rees@cu.edu)  
Ref.# CU2104B, 2396B, 2578B